مجموعة جولدن اكستريم
GOLDEN EXTREME GROUP

FALCON® TYRES

Passenger, SUV & Light-Truck Tyres

Product catalogue · size and load data for dealers and fleets

2026



PASSENGER CAR | ULTRA-HIGH PERFORMANCE | SUV HIGHWAY | SUV ALL-TERRAIN | VAN & LIGHT TRUCK

goldenextreme.com · +971 4 222 9799 · info@goldenextreme.com

Dubai · Sharjah

Contents

01 About Golden Extreme & Falcon 03

02 Range at a glance & how to read the tables 04

03 Passenger car 05

- FT 777 06
- FT 80 07
- FT 079 08
- FT 070 09

04 Ultra-high performance 10

- FT 888 11
- FT 998 12

05 SUV highway 13

- Primacy 77 14
- F/T 22 15
- FT 778 16
- FT 9087 17
- FT 9089 18

06 SUV all-terrain 19

- FT 9001 20
- FT 9009 21
- FT 097 22

07 Van & light truck 23

- Super 10 24
- Super 12 25
- FT 921 26
- FT 091 27
- FT 092 28
- FT 083 29
- FT 683 30
- Sand Grip 31

08 Contacts 32

مجموعة جولدن اكستريم

GOLDEN EXTREME GROUP

Founded 2014 · Dubai · Sharjah

FALCON TYRE

ABOUT US

Golden Extreme Group

Founded in 2014, Golden Extreme Group is a tyre and battery wholesaler with branches in Deira, Dubai and in Sharjah. From a single vision to a growing distribution network, the group has become a driving force in the UAE's tyre sector.

With 150,000+ sq ft of warehouse space, 120+ sales points and a dedicated team supported by an in-house engineer, we give fleets, tyre shops and dealers fast access to tyre solutions and dependable technical support.

Guided by the values of a family-built business, we continue to support our customers with reliable products, innovation and customer care.

OUR HOUSE BRAND

Falcon® Tyres

In the challenging landscapes of the Middle East and North Africa, where scorching heat meets endless roads, Falcon was created as a symbol of strength. Inspired by the UAE's national bird, the brand stands for sharp vision, speed and resilience.

Falcon was founded with a mission to offer tyres built for the region: PCR, TBR, OTR and light-truck ranges for desert, rugged terrain and modern city routes alike.

Falcon: engineered for the region, trusted on every journey.

2014
Founded

150,000+
sq ft warehouse space

120+
sales points

2
branches: Deira, Dubai & Sharjah

Our brands. Falcon® and Tubroo® are house brands of Golden Extreme Group. Golden Extreme is also the exclusive UAE agent for YOMAR Tyres.



RANGE AT A GLANCE

22 Falcon patterns, 5 categories

Every size in this catalogue is taken from the Falcon PCR source data. Each pattern page shows the full size table with load and speed index, tread depth, standard rim, inflated dimensions, maximum load and inflation pressure.

CATEGORY	PATTERN	SIZES	RIM Ø	LOAD INDEX	SPEED SYMBOLS	PAGE
PASSENGER CAR	**FT 777**	34	13″–16″	72–98	H, T, V	06
	FT 80	42	12″–15″	60–96	H, L, N, Q, S, T, V	07
	FT 079	10	12″–14″	65–95	Q, T	08
	FT 070	5	14″–15″	82–88	H, T	09
ULTRA-HIGH PERFORMANCE	**FT 888**	25	15″–18″	84–100	H, V, W	11
	FT 998	20	16″–20″	87–107	V, W	12
SUV HIGHWAY	**Primacy 77**	4	18″–20″	105–116	H, V	14
	F/T 22	14	15″–18″	108–116	H, R, S, T	15
	FT 778	25	15″–18″	96–116	H, T, V	16
	FT 9087	8	16″–18″	110–116	T	17
	FT 9089	4	17″–20″	112–116	H, V	18
SUV ALL-TERRAIN	**FT 9001**	40	13″–18″	85–126	H, R, S, T	20
	FT 9009	4	16″–17″	117–123	Q	21
	FT 097	4	15″	101–116	S	22
VAN & LIGHT TRUCK	**Super 10**	2	14″–15″	104–106	—*	24
	Super 12	25	14″–16″	96–118	Q, R, S	25
	FT 921	13	12″–16″	81–118	Q, R	26
	FT 091	4	14″–15″	100–106	Q	27
	FT 092	7	14″–15″	100–112	Q	28
	FT 083	8	13″–15″	92–101	N	29
	FT 683	3	16″–17″	111–118	Q, S	30
	Sand Grip	1	16″	107–112	R	31

C Commercial (van) tyre

PR Ply rating (load range)

ZR Speed rating above 240 km/h

Rim Standard measuring rim (in)

—* Contact sales for this value

LT Light-truck tyre

XL Extra-load (reinforced) tyre

a/b Load index single / dual fitment

kPa Inflation pressure at max. load

03

PCR · PASSENGER CAR RADIAL

Passenger car

Falcon PCR (Passenger Car Radial) tyres are engineered specifically for passenger cars, balancing comfort, durability and road stability. Radial construction gives strong grip, smooth handling and reliable performance for everyday driving.



FT 777 06

34 sizes · 13"–16"



FT 80 07

42 sizes · 12"–15"



FT 079 08

10 sizes · 12"–14"



FT 070 09

5 sizes · 14"–15"

PCR · PASSENGER CAR RADIAL

FT 777

Economy / comfort car tyre · energy-saving and comfortable driving

SIZES	RIM	LOAD INDEX
34	13"–16"	72–98



KEY FEATURES

- 4 longitudinal grooves combined with through-type lateral grooves improve hydroplaning and wet performance.
- Multi-pitch, variable-pitch arrangement with crossing sipes reduces vibration for ride comfort.
- Variable-angle lateral grooves reduce the air-pumping effect for quiet running.
- Reinforcing ribs reduce pattern deformation during acceleration, braking, steering and cruising, and stiffen the crown for handling.
- Wear-resistant compound and uniform contact-patch pressure increase tread wear life.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
155/65R13	73T	7.0	4.50B	532	157	365	300
165/65R13	77T	7.0	5.00B	544	170	412	300
175/60R13	77T	6.8	5.00B	540	177	412	300
175/70R13	82T	7.0	5.00B	576	177	475	300
185/70R13	86T	7.0	5.50B	590	189	530	300
165/55R14	72H	7.0	5J	538	170	355	300
165/60R14	75H	7.0	5J	554	170	387	300
165/65R14	79H	7.0	5J	570	170	437	300
165/70R14	81H	7.0	5J	588	170	462	300
175/65R14	82H	7.5	5J	584	177	475	300
175/70R14	84T	7.0	5J	602	177	500	300
185/60R14	82H	7.0	5½J	578	189	475	300
185/65R14	86H	7.2	5½J	596	189	530	300
185/70R14	88T	7.2	5½J	616	189	560	300
195/60R14	86H	7.0	6J	590	201	530	300
195/70R14	91T	7.2	6J	630	201	615	300
205/60R14	88H	7.0	6J	602	209	560	300
165/50R15	72H	7.0	5J	547	170	355	300
175/50R15	75H	7.0	5½J	557	182	387	300
185/55R15	82H	7.0	6J	585	194	475	300
185/65R15	88H	7.5	5½J	621	189	560	300
195/50R15	82H	7.0	6J	577	201	475	300
195/55R15	85V/H	7.0	6J	595	201	515	300
195/60R15	88H	7.0	6J	615	201	560	300
195/65R15	91H	7.5	6J	635	201	615	300
205/60R15	91H	7.0	6J	627	209	615	300
205/65R15	94H	7.2	6J	647	209	615	300
175/55R16	80H	7.0	5½J	598	182	450	300
185/55R16	83H	7.0	6J	610	194	487	300
205/55R16	91H	6.8	6½J	632	214	615	300
205/60R16	92V	7.5	6J	652	209	630	300
215/60R16	95V/H	7.5	6½J	664	221	690	300
215/65R16	98H	7.5	6½J	686	221	750	300
225/60R16	98H	7.5	6½J	676	228	750	300

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

PCR · PASSENGER CAR RADIAL

FT 80

Steering freely, enjoy the serenity

SIZES	RIM	LOAD INDEX
42	12"–15"	60–96



KEY FEATURES

- 4 main grooves of different widths combined with lateral grooves improve hydroplaning and wet performance.
- Centre rib enhances stability on dry roads, high-speed response and straight-line performance.
- Interchangeable grooves reduce pattern-block noise; circular-arc shoulder prevents damage from partial (uneven) wear.
- Random pitch configuration with five pitch sizes reduces noise; sipes and multi-pitch design add ride comfort.
- Jointless cap-ply strip ensures tyre uniformity; single hexagonal bead ring increases bead stability and durability.
- Optimised profile and component distribution for good steering and ride comfort.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
155/70R12	73T	7.4	4.50B	523	157	365	250
165/70R12	77T	7.5	5.00B	537	170	412	250
135/80R13	60L	5.0	4.00B	546	138	250	240
135/80R13	74N XL	5.0	4.00B	546	138	375	340
145/60R13	66N	5.6	4.50B	504	150	300	300
145/80R13	75T	6.0	4.00B	562	145	387	300
145/80R13	79N XL	6.0	4.00B	562	145	437	340
155/65R13	73T	7.3	4.50B	532	157	365	250
155/70R13	75T	7.5	4.50B	548	157	387	250
155/80R13	79T	7.8	4.50B	578	157	437	240
165/55R13	70N	5.5	5.00B	512	170	335	300
165/65R13	77T	7.8	5.00B	544	170	412	250
165/70R13	79T	7.6	5.00B	562	170	437	250
165/70R13LT 6PR	88/86S	7.6	5.00B	562	170	560/530	375
165/70R13C 6PR	88/86S	7.6	5.00B	562	170	560/530	375
165/80R13	83T	7.7	4.50B	594	165	487	240
175/70R13	82T	8.0	5.00B	576	177	475	250
185/70R13	86T	7.7	5.00B	590	189	530	250
155/50R14	67T	5.6	5J	512	162	307	300
165/60R14	75H	7.4	5J	554	170	387	300
165/65R14	79H	7.0	5J	570	170	437	300
165/70R14	81T	7.6	5J	588	170	462	250
165/80R14	85T	7.3	4½J	620	165	515	300
175/65R14	82H	7.8	5J	584	177	475	250
175/70R14	84T	8.0	5J	602	177	500	250
175/70R14LT 6PR	95/93Q	8.0	5J	602	177	690/650	375
175/70R14C 6PR	95/93Q	8.0	5J	602	177	690/650	375
185/60R14	82H	7.8	5½J	578	189	475	250
185/65R14	86H	7.7	5½J	596	189	530	250
185/70R14	88T	7.8	5½J	616	189	560	250
195/60R14	86H	7.7	6J	590	201	530	250
195/70R14	91T	7.7	6J	630	201	615	250
205/60R14	88H	8.0	6J	602	209	560	300
185/60R15	84H	7.0	5½J	603	189	500	300
185/65R15	88H	7.0	5½J	621	189	560	300
195/50R15	82H/V	7.4	6J	577	201	475	300
195/55R15	85H/V	7.4	6J	595	201	515	300
195/60R15	88H	7.2	6J	615	201	560	300
195/65R15	91H	7.8	6J	635	201	615	250
205/60R15	91H/V	7.4	6J	627	209	615	300
205/65R15	94H	8.0	6J	647	209	670	250
215/65R15	96H	7.5	6½J	661	221	710	300

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

PCR · PASSENGER CAR RADIAL

FT 079

Easy driving, ensure safety

SIZES	RIM	LOAD INDEX
10	12"–14"	65–95



KEY FEATURES

- Good quietness for stable and comfortable driving.
- Handling responds sensitively in corners.
- Deep grooves and tread compound for endurance and long-lasting use.
- Random pitch configuration with five pitch sizes reduces noise; smaller pattern blocks with more pitch sequences improve ride comfort.
- Jointless cap-ply strip ensures uniformity; single hexagonal bead ring increases bead stability and durability.
- Optimised profile and component distribution for good steering and ride comfort.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
135/70R12	65Q	6.5	4.00B	495	138	290	250
145/70R12	69T	7.2	4.50B	509	150	325	250
145/80R12	74T	7.3	4.00B	537	145	375	300
175/70R12	80T	7.0	5.00B	551	177	450	300
165/70R13	79T	7.0	5.00B	562	170	437	300
175/70R13	82T	7.0	5.00B	576	177	475	300
185/70R13	86T	7.0	5.50B	590	189	530	300
185/65R14	86T	7.0	5½J	596	189	530	300
185/70R14	88T	7.0	5½J	616	189	560	300
205/70R14	95T	7.0	6J	644	209	690	300

Load index “a/b” = single / dual fitment. Max load “a/b” = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

PCR · PASSENGER CAR RADIAL

FT 070

Safe and reliable · excellent wear resistance

SIZES	RIM	LOAD INDEX
5	14"–15"	82–88



KEY FEATURES

- Balanced pattern design gives natural, stable steering, good braking and grip, and confident lane changes.
- Three wide longitudinal grooves improve hydroplaning performance.
- Variable pitch design reduces tyre noise and enhances ride comfort.
- Silica compound: new-generation tread compound (high-styrene SBR, nanometre carbon-black reinforcement and highly dispersed silica) improves high-speed and wet grip.
- Jointless nylon cap over the steel belt enhances tread stiffness; higher sidewall turn-up gives two layers of protection against sidewall punctures.
- Wider contact area and deeper grooves improve tread life.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
175/70R14	88T XL	8.2	5J	602	177	560	340
185/60R14	82T	9.0	5½J	578	189	475	300
185/65R14	86T	9.0	5½J	596	189	530	300
185/65R15	88H	9.0	5½J	621	189	560	300
195/60R15	88H	9.0	6J	615	201	560	300

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

04

UHP

Ultra-high performance

Ultra-high-performance patterns for performance cars and sports saloons, in 15″ to 20″ rim sizes including ZR-rated and XL (extra load) fitments.



FT 888 11

25 sizes · 15″–18″



FT 998 12

20 sizes · 16″–20″

UHP

FT 888

Infinite passion, splendid experience

SIZES	RIM	LOAD INDEX
25	15"–18"	84–100



KEY FEATURES

- Four large longitudinal grooves reduce the influence of water for grip and stability on straight and curved wet roads; strong blocks enhance cornering traction.
- Strong continuous centre ribs ensure straight-line stability and acceleration; fine inside grooves speed up drainage on wet roads.
- Variable pitch pattern reduces tyre noise; optimised pattern improves straight-line and lateral grip.
- Silica compound: new-generation tread compound (high-styrene SBR, nanometre carbon-black reinforcement and highly dispersed silica) improves high-speed and wet grip.
- One nylon cap ply applied by jointless technique, single-wound hexagonal bead ring, double wide steel belts and HMLS polyester cord for strength, high-speed performance and puncture resistance.
- Optimised profile for handling and ride comfort; rim-guard design helps protect the rim from kerb contact.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
205/50R15	86V	8.0	6½J	587	214	530	300
205/55R15	88V	8.0	6½J	607	214	560	300
225/60R15	96V	8.3	6½J	651	228	710	300
195/50R16	84V	7.0	6J	602	201	500	300
195/55R16	91V XL	8.0	6J	620	201	615	340
195/60R16	89H	8.0	6J	640	201	580	300
205/55R16	91V	7.8	6½J	632	214	615	300
205/60R16	92V	8.0	6J	652	209	630	300
205/65R16	95H	8.0	6J	672	209	690	300
215/55ZR16	93W	8.0	7J	642	226	650	300
215/60R16	95V	8.1	6½J	664	221	690	300
215/65R16	98H	8.0	6½J	686	221	750	300
225/60R16	98H	8.3	6½J	676	228	750	300
235/60R16	100H	8.3	7J	688	240	800	300
205/40ZR17	84W XL	7.5	7½J	596	212	500	340
205/45ZR17	88W XL	7.5	7J	616	206	560	340
205/60R17	93V	7.5	6J	678	209	650	300
215/45ZR17	91W XL	7.5	7J	626	213	615	340
215/50ZR17	95W XL	8.0	7J	648	226	690	340
215/55ZR17	98W XL	8.0	7J	668	226	750	340
225/45ZR17	94W XL	8.0	7½J	634	225	670	340
225/50ZR17	98W XL	8.0	7J	658	233	750	340
225/55R17	97V	8.0	7J	680	233	730	300
225/45ZR18	95W XL	7.5	7½J	659	225	690	340
245/45ZR18	100W XL	7.5	8J	677	243	800	340

Highlighted rows: values corrected from the previous edition of this catalogue.
Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

UHP

FT 998

High performance UHP

SIZES	RIM	LOAD INDEX
20	16"–20"	87–107



KEY FEATURES

- UHP tyre for ride, handling, hydroplaning resistance, quiet performance and fuel economy.
- Large shoulder blocks and centre sipes optimise tread stiffness for high-speed handling.
- Continuous centre block for straight-line stability; three longitudinal grooves with lateral grooves for hydroplaning performance.
- Low-heat-generation, anti-slip compound improves fuel economy while ensuring wet grip and braking.
- Variable pitch design and optimised sipe arrangement for a smooth, low-noise ride.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
205/45R16	87V XL	7.4	7J	590	206	545	340
205/50ZR17	93W XL	7.4	6½J	638	214	650	340
205/55ZR17	95W XL	7.4	6½J	658	214	690	340
235/55ZR17	103W XL	7.4	7½J	690	245	875	340
215/55R18	95W	7.4	7J	693	226	690	300
225/40ZR18	92W XL	7.4	8J	637	230	630	340
225/50ZR18	99W XL	7.4	7J	683	233	775	340
235/45ZR18	94W	7.4	8J	669	236	670	300
235/45ZR18	98W XL	7.4	8J	669	236	750	340
235/50ZR18	101W XL	7.4	7½J	693	245	825	340
245/50ZR18	104W XL	7.4	7½J	703	253	900	340
225/45ZR19	96W XL	7.4	7½J	685	225	710	340
225/55ZR19	103W XL	7.4	7J	731	233	875	340
235/55R19	101W	7.4	7½J	741	245	825	300
245/40ZR19	98W XL	7.4	8½J	679	248	750	340
245/45ZR19	102W XL	7.4	8J	703	243	850	340
245/55ZR19	107W XL	7.4	7½J	753	253	975	340
245/45ZR20	103W XL	7.4	8J	728	243	875	340
245/40ZR20	99W XL	7.4	8½J	704	248	775	340
245/50ZR20	105W XL	7.4	7½J	754	253	925	340

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

05

SUV · HIGHWAY TERRAIN (HT)

SUV highway

Highway-terrain patterns for SUVs and 4x4s that spend most of their time on paved roads.



Primacy 77 14

4 sizes · 18"–20"



F/T 22 15

14 sizes · 15"–18"



FT 778 16

25 sizes · 15"–18"



FT 9087 17

8 sizes · 16"–18"



FT 9089 18

4 sizes · 17"–20"

SUV · HIGHWAY TERRAIN (HT)

PRIMACY 77

High performance SUV

SIZES	RIM	LOAD INDEX
4	18"–20"	105–116



KEY FEATURES

- High performance SUV tyre for comfort, quietness and durability.
- Four longitudinal grooves combined with sipes improve hydroplaning performance.
- Continuous centre block ensures steering and stability at high speed.
- Variable pitch design and optimised sipe arrangement for ride comfort and low noise.
- Large blocks and wide shoulder ribs give a stiff tread and uniform wear.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
265/65R18	114H	7.6	8J	801	272	1180	300
275/65R18	116H	7.6	8J	815	279	1250	300
255/50R20	105V	7.6	8J	764	265	925	300
285/50R20	116V XL	7.6	9J	794	297	1250	340

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

SUV · HIGHWAY TERRAIN (HT)

F/T 22

SUV tyre – highway terrain

SIZES	RIM	LOAD INDEX
14	15"–18"	108–116



KEY FEATURES

- Double "S" tread blocks improve grip and traction and reduce braking distance on dry and wet roads.
- Sharp-edged centre blocks break the water-surface tension to reduce sliding on wet roads.
- Wide contact patch and reinforced body construction improve impact resistance and load capability.
- Variable pitch sequence reduces driving noise.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
255/70R15C 6PR	112/110S	8.0	7½J	739	260	1120/1060	375
255/70R15LT 6PR	112/110S	8.0	7½J	739	260	1120/1060	375
255/70R15C 8PR	113/110S	8.0	7½J	739	260	1150/1060	450
205R16C 8PR	110/108R	9.5	6J	736	208	1060/1000	450
205R16LT 8PR	110/108R	9.5	6J	736	208	1060/1000	450
265/70R16	112T	8.0	8J	778	272	1120	300
275/70R16	114T	8.0	8J	792	279	1180	300
225/70R17	108T XL	8.0	6½J	748	228	1000	340
265/65R17	112S	8.3	8J	776	272	1120	300
275/65R17	115T	8.0	8J	790	279	1215	300
265/70R17	115T	8.0	8J	804	272	1215	300
285/65R17	116T	8.0	8½J	802	292	1250	300
265/60R18	110H	8.0	8J	775	272	1060	300
285/60R18	116T	8.0	8½J	799	292	1250	300

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

SUV · HIGHWAY TERRAIN (HT)

FT 778

Unimpeded journey, comfortable experience

SIZES	RIM	LOAD INDEX
25	15"–18"	96–116



KEY FEATURES

- Four large longitudinal grooves reduce water slip and keep straight, cornering and high-speed driving stable, with good wet drainage.
- Continuous centre ribs for straight-line stability and acceleration; large shoulder blocks enhance lateral grip.
- Multi-pitch pattern reduces driving noise for a quieter cabin.
- Silica compound: new-generation tread compound (high-styrene SBR, nanometre carbon-black reinforcement and highly dispersed silica) improves high-speed and wet grip.
- Jointless nylon cap over the steel belt, single-wound hexagonal bead ring, double wide steel belts and double-layer HMLS polyester cord for high-speed endurance, stability and puncture resistance.
- Optimised cross-section profile for handling and comfort; small apex with wear-resistant rubber improves bead stiffness and long-term load bearing.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
205/70R15	96T	8.1	6J	669	209	710	300
215/70R16	100H	8.5	6½J	708	221	800	300
225/70R16	103H	8.0	6½J	722	228	875	300
235/70R16	106H	8.3	7J	736	240	950	300
245/70R16	107H	8.1	7J	750	248	975	300
265/70R16	112H/T	8.5	8J	778	272	1120	300
275/70R16	114H/T	8.5	8J	792	279	1180	300
215/60R17	96H	8.5	6½J	690	221	710	300
215/65R17	99H	8.1	6½J	712	221	775	300
225/60R17	99H	8.5	6½J	702	228	775	300
225/65R17	102H	8.5	6½J	724	228	850	300
235/65R17	104H	8.5	7J	738	240	900	300
245/65R17	107H	8.5	7J	750	248	975	300
245/70R17	110T	8.1	7J	776	248	1060	300
265/65R17	112H	8.3	8J	776	272	1120	300
265/70R17	115H/T	8.5	8J	804	272	1215	300
225/55R18	98V	8.1	7J	705	233	750	300
225/60R18	100V	8.1	6½J	727	228	800	300
235/55R18	104V XL	8.1	7½J	715	245	900	340
235/60R18	107V XL	8.3	7J	739	240	975	340
245/60R18	105H	8.3	7J	751	248	925	300
255/70R18	113H	8.3	7½J	815	260	1150	300
265/60R18	110H	8.3	8J	775	272	1060	300
265/70R18	116T	8.1	8J	829	272	1250	300
275/70R18	116T	8.1	8J	843	279	1250	300

Highlighted rows: values corrected from the previous edition of this catalogue.
Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

SUV · HIGHWAY TERRAIN (HT)

FT 9087

SUV tyre – highway terrain

SIZES	RIM	LOAD INDEX
8	16"–18"	110–116



KEY FEATURES

- Cross-zigzag groove design improves grip, traction and braking on dry and wet roads.
- Optimised centre block design for stable handling.
- Interlocking tie-bars increase tread-block stiffness, prevent uneven wear and improve grip.
- Highly damage-resistant sidewall design improves passability on complex roads.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
265/70R16	112T	8.0	8J	778	272	1120	300
275/70R16	114T	8.0	8J	792	279	1180	300
265/65R17	112T	8.0	8J	776	272	1120	300
265/70R17	115T	8.0	8J	804	272	1215	300
265/60R18	110T	8.0	8J	775	272	1060	300
285/60R18	116T	8.0	8½J	799	292	1250	300
275/65R17	115T	8.0	8J	790	279	1215	300
285/65R17	116T	8.0	8½J	802	292	1250	300

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

SUV · HIGHWAY TERRAIN (HT)

FT 9089

SIZES	RIM	LOAD INDEX
4	17"–20"	112–116



KEY FEATURES

- 4 main grooves combined with through-type lateral grooves improve drainage and wet performance.
- Bars between the tread blocks increase stiffness and reduce pattern deformation during acceleration, braking and cornering.
- Variable pitch design with cross sipes reduces tread-block vibration for ride comfort.
- Multi-dimensional tread blocks offset and disperse noise between the blocks.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
245/75R17	112H	8.0	7J	800	248	1120	300
265/65R18	114H	8.0	8J	801	272	1180	300
285/65R18	116H	8.0	8½J	827	292	1200	300
265/55R20	113V	8.0	8½J	800	277	1150	300

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

06

SUV · ALL-TERRAIN (AT) & OFF-ROAD

SUV all-terrain

All-terrain and off-road patterns for SUVs and pickups, including LT (light truck) and 10PR fitments.



FT 9001 20

40 sizes · 13″–18″



FT 9009 21

4 sizes · 16″–17″



FT 097 22

4 sizes · 15″

SUV · ALL-TERRAIN (AT) & OFF-ROAD

FT 9001

Galloping on all terrain

SIZES	RIM	LOAD INDEX
40	13"–18"	85–126



KEY FEATURES

- AT pattern with 4 main longitudinal grooves, smooth transverse grooves and zigzag sipes for drainage and driving safety.
- 3D shoulder design gives an aggressive cross-country look.
- Variable-pitch design reduces tyre noise for a quiet drive.
- Special tread compound reduces wear and rolling resistance and increases traction on wet roads; deeper grooves increase tread life.
- Two steel belts and two plies enhance carcass strength; splice-free belt hoops tightly on the nylon cord; hexagonal bead ring for bead safety and endurance.
- Upgraded profile and material distribution for handling and ride comfort.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
175/75R13	85T	8.2	5.00B	592	177	515	300
175/80R14	88T	8.2	5J	636	177	560	300
LT215/75R14 6PR	98/95S	10.5	6J	678	216	750/690	350
205/60R15	91H	8.8	6J	627	209	615	300
205/65R15	94H	8.8	6J	647	209	670	300
205/70R15	96T	8.8	6J	669	209	710	300
205/75R15	97T	8.8	5½J	689	203	730	300
225/70R15	100T	9.3	6½J	697	228	800	300
225/70R15LT	107/103S	9.3	6½J	697	228	975/875	450
31X10.50R15LT	109S	11.5	8½J	775	268	1030	350
31X10.50R15LT	114/111R	11.5	8½J	775	268	1180/1090	550
LT235/75R15	104/101R	11.5	6½J	733	235	900/825	350
205/60R16	92H	8.8	6J	652	209	630	300
215/65R16	98T	8.8	6½J	686	221	750	300
215/70R16	100T	8.8	6½J	708	221	800	300
225/70R16	103T	9.3	6½J	722	228	875	300
235/60R16	100T	9.3	7J	688	240	800	300
235/70R16	106T	9.3	7J	736	240	950	300
245/70R16	107T	9.3	7J	750	248	975	300
255/70R16	111T	9.3	7½J	764	260	1090	300
265/70R16	112T	9.3	8J	778	272	1120	300
LT215/85R16	115/112R	11.5	6J	772	216	1215/1120	550
LT225/75R16	115/112R	11.5	6J	744	223	1215/1120	550
LT235/85R16	120/116R	11.5	6½J	806	235	1380/1260	550
LT245/70R16	120/116R	9.3	7J	750	248	1380/1260	550
LT245/75R16	120/116R	11.5	7J	774	248	1380/1260	550
LT265/70R16	121/118R	9.3	8J	778	272	1450/1320	550
LT265/70R16	123/120R	9.3	8J	778	272	1550/1400	550
LT265/75R16	123/120R	11.5	7½J	804	267	1550/1400	550
215/60R17	96T	8.8	6½J	690	221	710	300
225/60R17	99T	9.3	6½J	702	228	775	300
225/65R17	102T	9.3	6½J	724	228	850	300
235/60R17	102T	9.3	7J	714	240	850	300
235/65R17	104T	9.3	7J	738	240	900	300
245/70R17	110T	9.3	7J	776	248	1060	300
265/65R17	112T	9.3	8J	776	272	1120	300
265/70R17	115T	9.3	8J	804	272	1215	300
LT265/65R17	120/117R	9.3	8J	776	272	1400/1285	550
LT285/70R17	126/123R	11.5	8½J	832	292	1700/1550	550
265/60R18	110T	9.3	8J	775	272	1060	300

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

SUV · ALL-TERRAIN (AT) & OFF-ROAD

FT 9009

SIZES	RIM	LOAD INDEX
4	16"–17"	117–123



KEY FEATURES

- Optimised tread pattern, cavity and carcass design for stronger load bearing and off-road performance.
- Special groove bottom and stepped pattern design help eject stones.
- Independent tread blocks with increased gaps and lateral grooves for traction on mud and snow.
- Strengthened shoulder blocks and 3D sidewall improve passability and puncture resistance in harsh conditions.
- Variable pitch arrangement reduces pattern noise and improves ride.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
LT265/70R16 10PR	121/118Q	12.5	8J	778	272	1450/1320	550
LT265/75R16 10PR	123/120Q	12.5	7½J	804	267	1550/1400	550
LT265/65R17 10PR	120/117Q	12.5	8J	776	272	1400/1285	550
LT265/70R17 10PR	121/118Q	12.5	8J	804	272	1450/1320	550

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

SUV · ALL-TERRAIN (AT) & OFF-ROAD

FT 097

SIZES	RIM	LOAD INDEX
4	15"	101–116



KEY FEATURES

- High-tensile-strength plies improve high-speed performance on complicated road surfaces.
- Wavy groove design lets the pattern grip effectively on different road surfaces.
- Randomised groove distribution reduces running noise.
- Tread blocks of various sizes improve traction and ride comfort.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
235/75R15C 6PR	104/101S	12.0	6½J	733	235	900/825	350
235/75R15LT 6PR	104/101S	12.0	6½J	733	235	900/825	350
235/75R15C 10PR	116/113S	12.0	6½J	733	235	1250/1150	550
235/75R15LT 10PR	116/113S	12.0	6½J	733	235	1250/1150	550

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

07

VAN · LIGHT TRUCK (C / LT)

Van & light truck

Commercial (C) and light-truck (LT) patterns for vans, pickups and light commercial vehicles, in 8PR and 10PR load ranges.



Super 10 24
2 sizes · 14"–15"



Super 12 25
25 sizes · 14"–16"



FT 921 26
13 sizes · 12"–16"



FT 091 27
4 sizes · 14"–15"



FT 092 28
7 sizes · 14"–15"



FT 083 29
8 sizes · 13"–15"



FT 683 30
3 sizes · 16"–17"



Sand Grip 31
1 size · 16"

VAN · LIGHT TRUCK (C / LT)

SUPER 10

SIZES	RIM	LOAD INDEX
2	14"–15"	104–106



KEY FEATURES

The source catalogue lists sizes only for this pattern. Please contact our sales team for application advice.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
195R14C	106/104 —*	8.5	5½J	666	198	950/900	450
195R15C	106/104 —*	8.5	5½J	—*	198	950/900	450

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

—* Contact sales for this value.
Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

VAN · LIGHT TRUCK (C / LT)

SUPER 12

Steering freely, enjoy the serenity

SIZES	RIM	LOAD INDEX
25	14"–16"	96–118



KEY FEATURES

- 4 main grooves of different widths combined with lateral grooves improve hydroplaning and wet performance.
- Centre rib enhances stability on dry roads, high-speed response and straight-line performance.
- Interchangeable grooves reduce pattern-block noise; circular-arc shoulder prevents damage from partial (uneven) wear.
- Random pitch configuration with five pitch sizes reduces noise; sipes and multi-pitch design add ride comfort.
- Jointless cap-ply strip ensures tyre uniformity; single hexagonal bead ring increases bead stability and durability.
- Optimised profile and component distribution for good steering and ride comfort.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
185R14C 8PR	102/100Q	8.5	5½J	652	189	850/800	450
195R14LT 8PR	105/103Q	9.2	5½J	668	196	925/875	450
195R14C 8PR	106/104Q	9.2	5½J	668	196	950/900	450
205R14LT 8PR	107/105R	9.4	6J	684	208	975/925	450
205R14C 8PR	109/107R	9.4	6J	684	208	1030/975	450
215R14LT 8PR	110/108R	9.6	6J	700	218	1060/1000	450
215R14C 8PR	112/110R	9.6	6J	700	218	1120/1060	450
215/75R14LT 8PR	104/101Q	9.2	6J	678	216	900/825	450
215/75R14C 8PR	112/110Q	9.2	6J	678	216	1120/1060	475
185R15LT 8PR	103/102S	8.7	5½J	677	189	875/850	450
185R15C 8PR	103/102S	8.7	5½J	677	189	875/850	450
195R15LT 8PR	106/104Q	9.2	5½J	693	196	950/900	450
195R15C 8PR	106/104Q	9.2	5½J	693	196	950/900	450
195/65R15C 8PR	98/96R	8.8	6J	635	201	750/710	375
195/70R15LT 8PR	99/96R	8.8	6J	655	201	775/710	450
195/70R15C 8PR	104/102R	8.8	6J	655	201	900/850	450
205/70R15C 8PR	106/104R	8.8	6J	669	209	950/900	450
215/70R15C	109/107R	9.2	6½J	683	221	1030/975	450
225/70R15LT 8PR	106/103R	8.8	6½J	697	228	950/875	450
225/70R15C 8PR	112/110R	8.8	6½J	697	228	1120/1060	450
215/75R16C 8PR	113/111R	9.2	6J	728	216	1150/1090	475
225/65R16C 8PR	112/110R	9.2	6½J	698	228	1120/1060	475
225/75R16C 8PR	116/114R	9.2	6J	744	233	1250/1180	475
225/75R16C 10PR	118/116R	9.2	6J	744	233	1320/1250	525
235/65R16C 8PR	115/113R	9.2	7J	712	240	1215/1150	475

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

VAN · LIGHT TRUCK (C / LT)

FT 921

SIZES	RIM	LOAD INDEX
13	12"–16"	81–118



KEY FEATURES

- 3 deep longitudinal grooves for hydroplaning performance and handling stability, with reduced noise and wear.
- Continuous shoulder ribs give smooth, even tread wear and longer tread life.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
5.00R12C 8PR	83/81Q	8.0	3.50B	568	143	487/462	450
5.00R12C 10PR	88/86Q	8.0	3.50B	568	143	560/530	500
145R12C 8PR	86/84Q	7.5	4.00B	542	147	530/500	450
195R14C 8PR	106/104Q	8.5	5½J	666	198	950/900	450
195R15C 8PR	106/104Q	8.5	5½J	690	198	950/900	450
205/70R15C 10PR	107/103R	8.5	6J	669	209	975/875	550
225/70R15C 10PR	116/114R	8.5	6½J	697	228	1250/1180	525
195/75R16C 8PR	107/105R	9.2	5½J	698	196	975/925	475
195/75R16C 10PR	110/108R	9.2	5½J	698	196	1060/1000	525
205/75R16C 10PR	113/111R	9.2	5½J	714	203	1150/1090	525
215/75R16C 10PR	116/114R	8.5	6J	728	216	1250/1180	525
215/70R16C 6PR	108/106R	9.2	6½J	708	221	1000/950	375
225/75R16C 10PR	118/116R	8.5	6J	744	223	1320/1250	525

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

VAN · LIGHT TRUCK (C / LT)

FT 091

SIZES	RIM	LOAD INDEX
4	14"–15"	100–106



KEY FEATURES

- 3 wavy main grooves break the water-surface tension to disperse water for wet handling.
- Central tread blocks designed to reduce noise for driver and passengers.
- 3D blocks in the centre combined with lateral grooves for traction in various road conditions.
- High-stiffness shoulder blocks prevent profile deflection for more even treadwear and longer tyre life.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
185R14C 8PR	102/100Q	8.5	5½J	650	188	850/800	450
185R14LT 8PR	102/100Q	8.5	5½J	650	188	850/800	450
195R14C	106/104Q	8.5	5½J	666	198	950/900	450
195R15C	106/104Q	8.5	5½J	690	198	950/900	450

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

VAN · LIGHT TRUCK (C / LT)

FT 092

SIZES	RIM	LOAD INDEX
7	14"–15"	100–112



KEY FEATURES

- Three longitudinal grooves greatly enhance drainage on wet roads.
- Interlaced shoulder blocks promote cross-country performance.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
185R14C 8PR	102/100Q	8.5	5½J	650	188	850/800	450
195R14C 8PR	106/104Q	8.5	5½J	666	198	950/900	450
205R14LT 8PR	107/105Q	9.5	6J	686	208	975/925	450
205R14C 8PR	109/107Q	9.5	6J	686	208	1030/975	450
215R14LT 8PR	110/108Q	10.5	6J	700	218	1060/1000	450
215R14C 8PR	112/110Q	10.5	6J	700	218	1120/1060	450
195R15C 8PR	106/104Q	8.5	5½J	693	196	950/900	450

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

VAN · LIGHT TRUCK (C / LT)

FT 083

SIZES	RIM	LOAD INDEX
8	13"–15"	92–101



KEY FEATURES

- 4 longitudinal grooves for hydroplaning and wet performance.
- Strengthened shoulder improves high-speed steering while reducing wear.
- Multi-pitch arrangement reduces tyre noise for a quiet drive.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
6.00R13LT 10PR	98/93N	9.8	4.50E	655	175	750/650	560
6.00R13C 10PR	98/93N	9.8	4.50E	655	175	750/650	560
6.00R14LT 10PR	100/95N	9.8	4.50E	680	175	800/690	560
6.00R14C 10PR	100/95N	9.8	4.50E	680	175	800/690	560
6.00R15LT 8PR	97/92N	9.8	4.50E	705	175	730/630	460
6.00R15C 8PR	97/92N	9.8	4.50E	705	175	730/630	460
6.00R15LT 10PR	101/97N	9.8	4.50E	705	175	825/730	560
6.00R15C 10PR	101/97N	9.8	4.50E	705	175	825/730	560

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

VAN · LIGHT TRUCK (C / LT)

FT 683

SIZES	RIM	LOAD INDEX
3	16"–17"	111–118



KEY FEATURES

- Three-zigzag main grooves spread stress evenly and help eject stones, avoiding groove wear.
- Continuous shoulder rib improves load-bearing capacity and avoids uneven wear.
- Lateral shoulder grooves dissipate heat to improve durability.

SIZE TABLE

Size	Load / speed index	Tread depth mm	Standard rim in	Inflated OD mm	Section width mm	Max load kg	Pressure kPa
7.50R16LT 8PR	114/112S	9.8	6.00G	805	215	1180/1120	475
7.50R17LT 10PR	116/111S	9.8	6.00G	805	215	1250/1090	560
225/95R16C 8PR	118/116Q	8.4	6J	834	223	1320/1250	450

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index “a/b” = single / dual fitment. Max load “a/b” = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

VAN · LIGHT TRUCK (C / LT)

SAND GRIP

SIZES	RIM	LOAD INDEX
1	16"	107–112



KEY FEATURES

The source catalogue lists sizes only for this pattern. Please contact our sales team for application advice.

SIZE TABLE

Size	Standard rim	LI / SR	Section width mm	Overall diameter mm	Max load single kg	Max load dual kg	Pressure kPa
750R16C 8PR	6.00G	112/107R	215	805	1120	975	460

ORDERS & AVAILABILITY

Talk to our sales team

MAIN LINE
+971 4 222 9799

WHATSAPP
+971 58 649 8398

EMAIL
info@goldenextreme.com

Load index "a/b" = single / dual fitment. Max load "a/b" = single / dual (kg). XL = extra load. C = commercial, LT = light truck, PR = ply rating.

Talk to our sales team

مجموعة جولدن اكستريم

MAIN LINE	+971 4 222 9799
WHATSAPP	+971 58 649 8398
EMAIL	info@goldenextreme.com
WEB	goldenextreme.com

Deira, Dubai branch
Al Maktoum Hospital Rd, Naif, Deira, Dubai.
Mon–Thu & Sat 9:00–19:00, Fri 9:00–12:30, Sun closed.

Sharjah branch
Shop L18, Industrial Area 8, Al Nahda 1, Sharjah.
Sat–Thu 9:00–21:00, Fri closed.

FOUNDED 2014.

ALL CATALOGUES
goldenextreme.com/catalogues

ALSO FROM GOLDEN EXTREME

Falcon® and Tubroo® are house brands of Golden Extreme Group. Golden Extreme is the exclusive UAE agent for YOMAR Tyres. Ask our sales team for the Tubroo and Yomar ranges.

Specifications are subject to change without notice. Please confirm size, load index and availability with our sales team before ordering. © 2026 Golden Extreme Group.