مجموعة جولدن اكستريم
GOLDEN EXTREME GROUP

FALCON TYRE

FALCON® TYRES

Truck, Bus & OTR Tyres

Product catalogue · size and load data for dealers and fleets

2026



TRUCK & BUS RADIAL | SUPER SERIES | OFF-THE-ROAD (OTR)

goldenextreme.com · +971 4 222 9799 · info@goldenextreme.com

Dubai · Sharjah

Contents

01 About Golden Extreme & Falcon 03

02 Range at a glance & how to read the tables 04

03 TBR – Truck & bus radial (Super series) 05

Super 617 06	Super 527 06	Super 517 06
Super 668 07	Super 777 07	Super 580 07
Super 607 07	Super 608 08	Super 737 08
Super 619 08	Super 768 08	Super 613 09
Super 903 09	Super 44 09	Super 357 09
Super 98 10	Super 656 10	Super 329 10
Super 769 10	Super 904 11	Super 7 11
Super 8 11	Super 3 11	Super 6 12
Super 88 12	Super 2 12	Super 1 12

04 OTR – Off-the-road 13

Falcon OTR 13

05 Contacts 14

مجموعة جولدن اكستريم

GOLDEN EXTREME GROUP

Founded 2014 · Dubai · Sharjah

FALCON TYRE

ABOUT US

Golden Extreme Group

Founded in 2014, Golden Extreme Group is a tyre and battery wholesaler with branches in Deira, Dubai and in Sharjah. From a single vision to a growing distribution network, the group has become a driving force in the UAE's tyre sector.

With 150,000+ sq ft of warehouse space, 120+ sales points and a dedicated team supported by an in-house engineer, we give fleets, tyre shops and dealers fast access to tyre solutions and dependable technical support.

Guided by the values of a family-built business, we continue to support our customers with reliable products, innovation and customer care.

OUR HOUSE BRAND

Falcon® Tyres

In the challenging landscapes of the Middle East and North Africa, where scorching heat meets endless roads, Falcon was created as a symbol of strength. Inspired by the UAE's national bird, the brand stands for sharp vision, speed and resilience.

Falcon was founded with a mission to offer tyres built for the region: PCR, TBR, OTR and light-truck ranges for desert, rugged terrain and modern city routes alike.

Falcon: engineered for the region, trusted on every journey.

2014
Founded

150,000+
sq ft warehouse space

120+
sales points

2
branches: Deira, Dubai & Sharjah

Our brands. Falcon® and Tubroo® are house brands of Golden Extreme Group. Golden Extreme is also the exclusive UAE agent for YOMAR Tyres.



RANGE AT A GLANCE

27 Falcon TBR patterns + OTR

Every size in this catalogue is taken from the Falcon TBR source data. Patterns are listed in catalogue order; the source does not specify axle positions, so please ask our sales team for fitment advice.

PATTERN	SIZES	RIM Ø	LOAD INDEX	PR	PAGE
Super 617	8	20"–24"	142–160	16–20	06
Super 527	11	22.5"–24.5"	141–157	14–20	06
Super 517	3	22.5"–24"	154–164	20–22	06
Super 668	1	22.5"	160–160	20	07
Super 777	2	22.5"–24"	154–160	20	07
Super 580	3	22.5"–24"	150–162	20–22	07
Super 607	1	22.5"	149–152	18	07
Super 608	4	22.5"	143–157	16–20	08
Super 737	3	22.5"	149–157	18–20	08
Super 619	1	22.5"	160–160	20	08
Super 768	3	22.5"	143–157	16–20	08
Super 613	1	22.5"	160–160	20	09
Super 903	1	22.5"	149–152	18	09
Super 44	1	16"	114–118	14	09
Super 357	1	24.5"	146–149	16	09
Super 98	2	24"	157–162	20–22	10
Super 656	1	22.5"	143–146	16	10
Super 329	1	20"	153–156	20	10
Super 769	2	24"	157–164	20–22	10
Super 904	2	16"	118–132	14–18	11
Super 7	3	16"–17.5"	121–143	16–18	11
Super 8	5	16"–20"	105–139	12–16	11
Super 3	7	16"–22.5"	114–154	14–20	11
Super 6	5	16"–20"	114–144	14–16	12
Super 88	2	24"	156–162	22	12
Super 2	5	14"–16"	96–118	10–14	12
Super 1	4	17.5"–19.5"	132–143	18	12
Falcon OTR	7 (16 PR variants)	25"	–	12–36	13

LI / SR Load index / speed rating

PR Ply rating

TT / TL Tube type / tubeless

S / D Single / dual fitment

LT Light-truck size

Rim Standard rim width (in)

03

TBR · TRUCK & BUS RADIAL

Falcon TBR Tyres

Engineered for trucks, buses and heavy commercial vehicles, Falcon TBR tyres are built for high mileage, endurance and reliability, with the strength, load capacity and long-distance durability that demanding routes call for. Falcon TBR: drive with confidence.



S 617 06



S 527 06


S 517 06


S 668 07


S 777 07


S 580 07


S 607 07


S 608 08


S 737 08


S 619 08


S 768 08


S 613 09


S 903 09


S 44 09


S 357 09


S 98 10


S 656 10


S 329 10


S 769 10


S 904 11


S 7 11


S 8 11



S 3 11


S 6 12


S 88 12


S 2 12


S 1 12


OTR 13

Falcon Super series



SUPER 617

8 sizes · 20"–24"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
900R20	144/142L	16	15.5	7.00	2800/2650	900/900
1000R20	149/146K	18	15.5	7.50	3250/3000	930/930
1100R20	152/149K	18	16.5	8.00	3550/3250	930/930
1200R20	156/153K	20	17.5	8.50	4000/3650	900/900
1200R24	160/157K	20	16	8.50	4500/4125	900/900
11R22.5	146/143L	16	16	8.25	3000/2725	830/830
12R22.5	152/148M	18	15	9.00	3550/3250	930/930
315/80R22.5	157/154L	20	14.5	9.00	4000/3350	850/850



SUPER 527

11 sizes · 22.5"–24.5"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
11R22.5	144/142M	14	16	8.25	2800/2650	720/720
11R22.5	146/143L	16	16	8.25	3000/2725	830/830
12R22.5	152/149M	18	16.5	9.00	3550/3250	930/930
295/80R22.5	152/149L	18	16	9.00	3550/3250	900/900
315/80R22.5	157/154L	20	15	9.00	4125/3750	900/900
285/75R24.5	144/141M	14	15	8.25	2800/2575	760/760
285/75R24.5	147/144L	16	15	8.25	3075/2800	830/830
295/75R22.5	144/141M	14	15	9.00	2800/2575	760/760
295/75R22.5	146/143L	16	15	9.00	3000/2725	830/830
11R24.5	146/143M	14	15	8.25	3000/2725	720/720
11R24.5	149/146L	16	15	8.25	3250/3000	830/830



SUPER 517

3 sizes · 22.5"–24"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
12.00R24	160/157K	20	14.5	8.50	4500/4125	900/900
315/80R22.5	157/154L	20	14.5	9.00	4000/3350	850/850
325/95R24	164/162K	22	14.5	9.00	5000/4725	900/900

S / D = single / dual fitment. LI / SR = load index / speed rating.
Highlighted rows: values corrected from the previous edition of this catalogue.

Falcon Super series



SUPER 668

1 size · 22.5″

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
385/65R22.5	160K	20	15	11.75	4500	900



SUPER 777

2 sizes · 22.5″–24″

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
315/80R22.5	157/154F	20	23	9.00	4125/3750	900/900
12.00R24	160/157K	20	22.5	8.50	4500/4125	900/900



SUPER 580

3 sizes · 22.5″–24″

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
315/80R22.5	156/150M	20	16	9.00	4000/3350	850/850
12.00R24	160/157K	20	16	8.50	4500/4125	900/900
325/95R24	162/160K	22	16	9.00	5000/4725	900/900



SUPER 607

1 size · 22.5″

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
295/80R22.5	152/149L	18	18	9.00	3550/3150	850/850

S / D = single / dual fitment. LI / SR = load index / speed rating.

Falcon Super series



SUPER 608

4 sizes · 22.5"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
11R22.5	146/143L	16	22	8.25	3000/2725	830/830
12R22.5	152/149M	18	23	9.00	3550/3250	930/930
295/80R22.5	152/149L	18	23	9.00	3550/3250	850/850
315/80R22.5	157/154L	20	18	9.00	4000/3350	850/850



SUPER 737

3 sizes · 22.5"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
12R22.5	152/149M	18	22	9.00	3550/3250	930/930
295/80R22.5	152/149L	18	22	9.00	3550/3250	850/850
315/80R22.5	157/154L	20	22	9.00	4000/3350	850/850



SUPER 619

1 size · 22.5"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
385/65R22.5	160K	20	15	11.75	4500	900



SUPER 768

3 sizes · 22.5"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
11R22.5	146/143L	16	22	8.25	3000/2725	830/830
295/80R22.5	152/149L	18	23	9.00	3550/3250	900/900
315/80R22.5	157/154L	20	22	9.00	4000/3350	850/850

S / D = single / dual fitment. LI / SR = load index / speed rating.

Falcon Super series



SUPER 613

1 size · 22.5"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
385/65R22.5	160K	20	14.5	11.75	4500	900



SUPER 903

1 size · 22.5"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
295/80R22.5	152/149F	18	22	9.00	3550/3250	900/900



SUPER 44

1 size · 16"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
7.00R16LT	118/114L	14	11	5.50F	1320/1180	770/770



SUPER 357

1 size · 24.5"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
11R24.5	149/146M	16	22	8.25	3250/3000	830/830

S / D = single / dual fitment. LI / SR = load index / speed rating.

Falcon Super series



SUPER 98

2 sizes · 24″

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
12.00R24	160/157K	20	23	8.50	4500/4125	900/900
12.00R24	162/160K	22	23	8.50	4500/4125	900/900



SUPER 656

1 size · 22.5″

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
275/70R22.5	146/143L	16	14	8.25	3000/2725	900/900



SUPER 329

1 size · 20″

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
12.00R20	156/153K	20	21	8.50	4000/3650	900/900



SUPER 769

2 sizes · 24″

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
12.00R24	160/157K	20	23	8.50	4500/4125	900/900
325/95R24	164/162K	22	23	9.00	5000/4725	900/900

S / D = single / dual fitment. LI / SR = load index / speed rating.

Falcon Super series



SUPER 904

2 sizes · 16"

Size	LI / SR	PR	Tread depth mm	Standard rim	Max load S / D kg	Pressure S / D kPa
7.50R16LT	122/118K	14	15.5	6.00G	1500/1320	770/770
8.25R16LT	132/128K	18	15	6.50H	2000/1800	870/870



SUPER 7

3 sizes · 16"–17.5"

Size	PR	Load index	Speed	Standard rim	Section width mm	Outer diameter mm	Tread depth mm
750R16	16	125/121	L	6.00G	215	805	12.0
825R16	16	128/124	L	6.50H	235	855	13.0
9.5R17.5	18	143/141	K	6.75	240	842	12.0



SUPER 8

5 sizes · 16"–20"

Size	PR	Load index	Speed	Standard rim	Section width mm	Outer diameter mm	Tread depth mm
650R16	12	110/105	L	5.50F	185	750	10.0
700R16	14	118/114	L	5.50F	200	775	11.0
750R16	16	125/121	L	6.00G	215	805	12.0
825R16	16	128/124	L	6.50H	235	855	12.0
825R20	16	139/137	K	6.5	236	974	14.5



SUPER 3

7 sizes · 16"–22.5"

Size	PR	Load index	Speed	Standard rim	Section width mm	Outer diameter mm	Tread depth mm
700R16	14	118/114	M	5.50F (TT) / 5½J (TL)	200	775	10.0
8.5R17.5	16	126/124	M	6.00	215	802	11.0
225/80R17.5	16	129/127	M	6.75	226	805	11.0
265/70R19.5	18	143/141	K	7.50	262	867	14.5
275/80R22.5	18	149/146	M	8.25	276	958	14.5
295/60R22.5	18	150/147	K	9.00	292	926	15.0
295/80R22.5	20	154/151	L	9.00	298	1044	15.0

S / D = single / dual fitment. LI / SR = load index / speed rating.
Highlighted rows: values corrected from the previous edition of this catalogue.

Falcon Super series



SUPER 6

5 sizes · 16"–20"

Size	PR	Load index	Speed	Standard rim	Section width mm	Outer diameter mm	Tread depth mm
700R16	14	118/114	L	5.50F	200	775	12.0
750R16	16	125/121	L	6.00G	215	805	13.5
825R16	16	128/124	K	6.50H	235	855	13.5
825R20	16	139/137	J	6.5	236	974	16.0
900R20	16	144/142	J	7.0	259	1019	17.0



SUPER 88

2 sizes · 24"

Size	PR	Load index	Speed	Standard rim	Section width mm	Outer diameter mm	Tread depth mm
325/95R24	22	162/160	K	9.00	325	1228	16.5
1200R24	22	160/156	K	8.5	315	1226	16.5



SUPER 2

5 sizes · 14"–16"

Size	PR	Load index	Speed	Standard rim	Section width mm	Outer diameter mm	Tread depth mm
600R14	10	100/96	L	—*	170	680	10.0
600R15	10	101/97	L	—*	170	705	10.0
700R15	14	117/115	J	5.50F (TT) / 5½J (TL)	200	750	12.0
650R16	12	110/105	M	5.50F (TT) / 5½J (TL)	185	750	10.0
700R16	14	118/114	M	5.50F (TT) / 5½J (TL)	200	775	10.0



SUPER 1

4 sizes · 17.5"–19.5"

Size	PR	Load index	Speed	Standard rim	Section width mm	Outer diameter mm	Tread depth mm
215/75R17.5	18	135/133	J	6.00	211	767	11.5
235/75R17.5	18	143/141	J	6.75	233	797	11.5
245/70R17.5	18	134/132	M	7.50	248	789	11.5
245/70R19.5	18	141/140	J	7.50	248	839	14.0

S / D = single / dual fitment. LI / SR = load index / speed rating.
—* Contact sales for this value.

04 · OTR · OFF-THE-ROAD

Falcon OTR

Falcon OTR tyres are heavy-duty tyres for construction machines, mining equipment, loaders, dozers and similar machinery, made to handle rough and uneven terrain.

Service codes: E-3 / L-3 · 7 sizes on 25″ rims



SIZE TABLE

Size	PR	T.D. mm	S.R.	S.W. mm	O.D. mm	Max loading (kg)		Pressure (kPa)		Type
						50 km/h	10 km/h	50 km/h	10 km/h	
16.00-25	28	28.5	11.25/2.0	430	1495	6700	11500	575	750	TT/TL
	32					7300	12500	650	875	
	36					7750	13600	725	975	
15.5-25	12	24.5	12.00/1.3	395	1275	3250	5600	250	400	TT/TL
	16					3850	6750	325	525	
17.5-25	16	28	14.00/1.5	445	1350	4250	7300	300	475	TT/TL
	20					5000	8250	400	575	
20.5-25	20	30	17.00/2.0	520	1490	6000	9500	325	450	TT/TL
	24					6700	10300	400	525	
	28					7500	11500	475	625	
23.5-25	20	33	19.50/2.5	595	1615	7300	10900	300	375	TT/TL
	24					8000	12500	350	475	
	28					8750	13600	400	550	
26.5-25	28	35	22.00/3.0	675	1750	10000	15500	350	475	TL
	32					11200	17000	425	550	
29.5-25	28	38	25.00/3.5	750	1875	11500	17500	325	425	TL
	34					12500	19000	375	500	

T.D. = tread depth · S.R. = standard rim · S.W. = section width · O.D. = overall diameter · TT / TL = tube type / tubeless.

Talk to our sales team

مجموعة جولدن اكستريم

MAIN LINE	+971 4 222 9799
WHATSAPP	+971 58 649 8398
EMAIL	info@goldenextreme.com
WEB	goldenextreme.com

Deira, Dubai branch
Al Maktoum Hospital Rd, Naif, Deira, Dubai.
Mon–Thu & Sat 9:00–19:00, Fri 9:00–12:30, Sun closed.

Sharjah branch
Shop L18, Industrial Area 8, Al Nahda 1, Sharjah.
Sat–Thu 9:00–21:00, Fri closed.

FOUNDED 2014.

ALL CATALOGUES
goldenextreme.com/catalogues

ALSO FROM GOLDEN EXTREME

Falcon® and Tubroo® are house brands of Golden Extreme Group. Golden Extreme is the exclusive UAE agent for YOMAR Tyres. Ask our sales team for the Tubroo and Yomar ranges.

Specifications are subject to change without notice. Please confirm size, load index and availability with our sales team before ordering. © 2026 Golden Extreme Group.